

Tivoli



PRIMI  
CERAMICHE



For over 30 years **Primi Ceramiche** brand has been representing the best expression of Italian excellence and design applied to its products. **Porcelain floors and walls, for indoor and outdoor**, made with the aim of ensuring sturdiness and able to **preserve their beauty over time**.



The nuance of colours and the variety of available finishes for this collection allows to meet the needs of design and the taste of our customers.


## Sizes

600×600mm  
300×600mm  
300×300mm

## Finishes


Matt  
Polished

## Colours



## Mosaics

For most sophisticated we recommend **Mosaic Line**, custom solutions that we produce only upon request.



## Technical Characteristics

### GLAZED PORCELAIN TILES

TEST ITEM		REFERENCE STANDARD	STANDARD REQUIREMENTS	TEST RESULTS
WATER ABSORPTION		ISO 10545-3	1% - <3%	0,09%
BREAKAGE PRESSURE (N)		ISO 10545-4	≥1300N	2188N
SURFACE QUALITY		ISO 10545-2	95% of the tiles will not show any surface defects inspected with the naked eye from 1 meter distance	Conforming
SURFACE FLATNESS	Center bending strength	ISO 10545-2	±0.5	-0.07%~±0.03%
	Warpage	ISO 10545-2	±0.5	0~±0.16%
	Side bending strength	ISO 10545-2	±0.5	0~±0.17%
SIDE DEVIATION		ISO 10545-2	±0.6%	0~±0.13%
SIDE LENGH		ISO 10545-2	±0.6%	0~±0.13%
RECTANGULARITY		ISO 10545-2	±0.6%	0.08%~±0.08%
STRAIGHTNESS OF SIDES		ISO 10545-2	±0.5%	0.03%~±0.03%
RESISTANCE TO SURFACE ABRASION		ISO 10545-7	2100,6000,12000	CLASS 4 Failure visible at 2100 revolutions
SLIP RESISTANCE - WET DCOF VALUE		ANSI A137-1:2012	>0,42	0,14
RESISTANCE TO CHEMICAL		ISO 10545-13	MIN. GB	GA (V)
STAIN RESISTANCE		ISO 10545-14	MIN.CLASS 3	CLASS 5



Via L. Ariosto 30, 35128 Padova – ITALY  
+39 049 780 8487  
[info@expocasapadova.it](mailto:info@expocasapadova.it)